

BLA-L

Commercial Dehumidifier

Warehouse/ Workshop/ Wine cellar Power supply room/ File room/ Basement

Product details

1. G3 Filter Screen:

Extreme stamping process, able to filter a lot of air impurities, It can eff ectively reduce machine loss and prolong service life.

2. Large Wide-Angle Dehumidifying Surface : Greatly improve the area of dehumidifying. Effectively

3. Circulating Air System:

improve dehumidification efficiency.

The side outlet and the dehumidifying face are combined to improve the dehumidifying efficiency.

4. Human Engineering Handle:

Human Engineering Handles are set on both side, make it convenient to move and move machines.

5.Side Drain:

There is a drainage port on the side of the fuselage, which can continuously drain to prevent the water from flowing back to the machine.



Features

- 1. Three types of models for customers to choose
- 2. Automatic Restart after Power Failure
- 3. Automatic condensate pump with overflowprotection,
- 4. Timer switch function
- 5. Low temperature automatic defrost function
- 6. Hot-gas bypass technology for fast defrost







Specifications

Model	BLA-90L	BLA-138L	BLA-150L
Product Type	Commercial Dehumidifier		
Water Removal (L/D) (30°C-80%RH)	90L/D	138L/D	150L/D
Water Removal (L/D) (27°C-60%RH)	45L/D	65L/D	70L/D
Power Supply	220V~240V/50Hz		
Power Consumption	1075W	1215W	1495W
Air Volume	1000m3/H	1300m3/H	1500m3/H
Noise Level	<50db <55db		
Operating Range		5-38°C	
Applicable area	60-100m²	80-130m²	100-200㎡
Filter	G3 filter		
Drainage	Drainage pipe drainage		
Compressor	Rotary		
Refrigerant	R410a		
Humidity adjustment range	10%-90%RH		
Automatic defrost function	Low temperature automatic defrost function		
Compressor protection	Three-minute time delay protection		
Product Size	455*360*840mm	540*440*985 mm	540*440*985mm
Packing Size	540*440*895mm	625*520*1035mm	625*520*1035mm
Net Weight	42Kg	51Kg	63Kg
Gross Weight	45Kg	54Kg	72Kg
Customized Services	Support OEM/ODM		

Product Size

