

# ILE-L

## Rotational DEHUMIDIFIER

**Best performance**  
**Durable&Easy-transport**



### Features

- 1.Intelligent Electronic Control
- 2.Automatic Restartafter Power Failure
- 3.Automatic condensate pump with overflowprotection
- 4.Hot - gas bypass technology for fast defrost
- 5.Fastest access for cleaning and maintenance
- 6.Rotomolded plastic housing is super strong for resistance todamage
- 7.Metal handle with big wheels for easy transportation ·
- 8.Optional Continuous drainage hose and External Ducting



Control Panel



Big Wheels



Air Duct Connecting

### Color Options



# 02

### Specifications

Model	ILE-50L	ILE-70L	ILE-100L
Power Supply	110V/220V ~50Hz/60Hz		
Water Removal (30°C RH80%)	50L/day	70L/day	100L/day
Water Removal (27°C RH60%)	30L/day	40L/day	60L/day
Power Consumption	720W	815W	1,280W
Air Volume	420m³/h	500m³/h	1,000m³/h
Noise Level	55dB(A)	55dB(A)	60dB(A)
Compressor	Rotary	Rotary	Rotary
Refrigerant	R410A/R290	R290	R410A/R290
Operating Range	1~38°C	1~38°C	1~38°C
Outlet Size (Outer diameter)	160mm	160mm	220mm
Power Cord	5m	5m	5m
Drainage Pipe	5m	5m	5m
Net Weight	33.5 kg	39.2 kg	TBC
Gross Weight	36.5 kg	43.2 kg	TBC
Product Size	510 × 435 × 700 mm	570 × 500 × 800 mm	595 × 595 × 870 mm
Packing Size	560 × 500 × 760 mm	620 × 580 × 885 mm	620 × 650 × 960 mm

### Product Size

