

ILR-L

PROFESSIONAL WATER DAMAGE RESTORATION



Features

1. Superior stacking for storage
2. Ultra-compact, low weighted design
3. Hot-gas bypass technology for fast defrost
4. Fastest access for cleaning and maintenance
5. Intelligent electronic control
6. Intelligent & simple operate electronic control
7. Rugged rotomolded plastic housing resists scratches
8. Automatic condensate pump with over flow protection
9. Retractable handle with wheels for easy transportation
10. Optional external ducting can be connected



Specifications

Model	ILR-35L	ILR-55L	ILR-95L
Power Supply	220V~ 50Hz		
Water Removal (30°C RH80%)	35L/day	55L/day	95L/day
Water Removal (27°C RH60%)	20L/day	35L/day	55L/day
Power Consumption	475W	580W	950W
Air Volume	330m ³ /h	420m ³ /h	1,000m ³ /h
Noise Level	50dB(A)	55dB(A)	60dB(A)
Compressor	Rotary	Rotary	Rotary
Refrigerant	R290	R290	R290
Operating Range	1~38°C	1~38°C	1~38°C
Outlet Size (Outer diameter)	150mm	160mm	220mm
Power Cord	5m	5m	5m
Drainage Pipe	5m	5m	5m
Net Weight	22 kg	29.2 kg	44.8Kg
Gross Weight	23.5 kg	31.5 kg	47.8Kg
Product Size	310×500×370 mm	345×560×450 mm	705×450×530 mm
Packing Size	380×570×440 mm	415×620×520 mm	785×510×600 mm

Product Size

